

3 POINT HITCH ANGLE PLOW

AP 50, 55, 60, 72

Ideal for snow removal operations in urban areas, such as sidewalks and parking areas. The hydraulic relief valve prevents damage to the hydraulics when sudden impact or shock occurs. The cylinder bump stops prevent the cylinder from contracting and hitting the cylinder base. Made with a two-piece AR 400 cutting edge ensures unbeatable durability and strength. Offers up to a 30° angle that can be hydraulically or mechanically operated. Two trip edges keep the plow steady when hitting obstacles.



	AP50	AP55	AP60	AP72
Weight	525 lbs (240 kg)	550 lbs (250 kg)	575 lbs (261 kg)	720 lbs (328 kg)
Clearing Width	50" (127 cm)	55" (140 cm)	60" (152 cm)	72" (183 cm)
Clearing Width at 30°	43.3" (109 cm)	47.6" (121 cm)	52" (132 cm)	62.3" (158 cm)
Overall Width	50" (127 cm)	55" (140 cm)	60" (152 cm)	72" (183 cm)
Overall Height	36" (92 cm)			
Mouldboard Height	27" (68 cm)			
Swing Angle	30°			
Cutting Edges	Rubber, UHMW, Mild steel, Stainless steel, Corundum, PU, Vulcalon, Carbide, AR 400			
Power Requirements	40 HP (30 kW) - 93 HP (70 kW)			
Standard Features	AR 400 cutting edge, hydraulic angling, rubber deflector			
Hitch Category	CAT I or CAT II			
Options	LED working lights, Curb wear block, Marker flags, Manual angling of blade, Custom colours, liquid paint. Other sizes available please inquire.			

BUILT TO LAST

METEC METAL TECHNOLOGY INC.