COMPACT ANGLE PLOW

APC 48, 55, 60

With weight reduction in mind this angle plow is simple and ideal for snow removal operations in urban areas, such as sidewalks and parking areas. The hydraulic relief valve prevents damage to the hydraulics when sudden impact or shock occurs. The cylinder bump stops prevent the cylinder from contracting and hitting the cylinder base. Made with a one-piece cutting edge designed with a full trip edge ensures unbeatable durability and strength. Offers up to a 30° angle that can be hydraulically or mechanically operated.



_		_	
	APC48	APC55	APC60
Weight	315 lbs (143 kg)	358 lbs (162 kg)	368 lbs (167 kg)
Clearing Width	48" (122 cm)	55" (140 cm)	60" (152 cm)
Clearing Width at 30°	41.6" (106 cm)	47.6" (121 cm)	52" (132 cm)
Overall Width	49.5" (126 cm)	56.5" (144 cm)	61.5" (156 cm)
Overall Height	23" (58.5 cm)		
Mouldboard Height	21.5" (54.5 cm)		
Swing Angle	30°		
Cutting Edges	Rubber, UHMW, Mild steel, Stainless steel, Corrundum, PU, Vulcalon, Carbide, AR 400		
Power Requirements	20 HP (15 kW)		
Standard Features	UHWM cutting edge, Hydraulic angling, Oscillation		
Hitch Category	A Frame, Custom available		
Options	Marker flags, Manual angling of blade, Custom colours, liquid paint. Other sizes available please inquire.		