

THREE-POINT SPREADER

D 301, 601

Kugelmann's new generation of one-chamber three-point spreaders. The innovative material combination of stainless steel and high-quality plastic has unbeatable durability and reliability. The spreading width ranges from 39" to 276" (1 to 7 m) and can be adjusted electronically. Equipped with a three-point hitch, this spreader can be mounted on most tractors. The parking stand provided allows for easy parking and storage.



	D 301	D 601
Weight	392 lbs (178 kg)	492 lbs (223 kg)
Capacity	0.4 cu yd (300 ℓ)	0.78 cu yd (600 ℓ)
Spreading Width	39-276" (1-7 m)	
Overall Height	50" (127 cm)	54" (137 cm)
Overall Width	43" (108 cm)	53" (135 cm)
Overall Length	32" (82 cm)	
Hitch Category	3PH CAT I	
Standard Features	Parking Stand, Screw Conveyor for exact amounts, K-Tronic 1	
Options	Agitator shaft, K-Tronic 2 control system	

K-TRONIC 2 offers a data recording feature for archiving of spreading data or GPS data. Choose your infinitely variable spread width or adjust the spread pattern in an asymmetric way, e.g. for spreading along the kerbside and mix your spreading material in any proportion.



BUILT TO LAST

METAL TECHNOLOGY INC.

METEC