

FRONT BOOM MOWER

KKM

The KKM front boom mower, boasting over a 138" (3.5 m) reach, is designed for road vegetation maintenance. Its compact size and compatibility with small municipal vehicles make it ideal for urban, rural, and hard-to-reach areas. The KKM features a front frame with slide rails, supporting two hydraulically operated arms and a mowing head at the top of the upper arm. The mowing side can be easily changed, and the equipment is versatile, accommodating different mowing heads and hedge trimmers.



KKM	
Depth	45.6" (1.2 m)
Transportation Width	66.9" (1.7 m)
Transportation Height	49.2" (1.3 m)
Sliding Area	51.2" (1.3 m) – Horizontal movement of boom arm
Max Reach from Centre	139.8" (3.6 m)
Cutting Width	39.4" (1 m)
Attachments	Mowing head and Hedge trimmer
Standard Features	SelectMotion control system, mowing on both sides, made from high quality steel
Options	TotalMotion control system, Counterweight with storage legs with jacks and wheels

Intuitive control systems

Depending on the terrain, and user preferences, there are two control systems available:

SelectMotion

Selective proportional control makes it easy to operate the mower's boom arm and working tool on tough terrains. When you move the joystick, it activates a specific hydraulic cylinder, meaning you need to move the joystick more to position the boom arm where you'd like it.

TotalMotion

Fully proportional control is designed for challenging terrains with obstacles, requiring constant maneuvering of the boom arms. Using the joystick enables swift adjustments to the boom arm position by moving multiple cylinders with a single joystick motion.