

HYDRAULIC RIBBON BLOWER - BIG

L 1600, 1800, 2000

Professional two-phase snow turbine suitable for medium/large capacity tractors can be mounted to the front or rear, with a three-point hitch. Heavy-duty serrated augers, lever adjustable skid shoes, galvanized steel chute, hydraulic chute rotation, and deflector adjustment. Applicable to front and rear ends, with a three-point hitch. Heavy-duty serrated augers cut through the toughest hard-packed snow and ice. Adjustable skid shoes allow you to adjust the height of the cutting edge to save blowing gravel off of the pathway. Hydraulic chute rotation and deflector adjustment allow you to make adjustments without leaving the tractor cab.



	L 1600	L 1800	L 2000
Weight	1,345 lbs (610 kg)	1,477 lbs (670 kg)	1,609 lbs (730 kg)
Clearing Width	63" (160 cm)	71" (180 cm)	79" (200 cm)
Overall Width	65" (165 cm)	73" (185 cm)	80.5" (205 cm)
Intake Height		37.5" (95 cm)	
Overall Height		75" (190 cm)	
Cutting Auger Diameter		24" (61 cm)	
Oil Requirements	32/42 GPM (120/160 l/min)	34/42 GPM (130/160 l/min)	37/42 GPM (140/160 l/min)
Impeller Diameter		24.5" (62 cm)	
Standard Features	Reinforced frame, radial piston hydraulic motor, steel gearbox, auger with welded supports and ice breaker, hydraulic chute rotation, hydraulic chute deflector adjustment, tippable chute.		
Hitch Category	Set-up for mounting plate or similar		
Options	Fully-adjustable chute in galvanized iron, automatic safety torque limiters on auger, swinging connection with hydraulic control.		

BUILT TO LAST

METEC METAL TECHNOLOGY INC.