

# HYDRAULIC RIBBON BLOWER - MIDDLE

L 1300, 1400, 1500, 1600

Suitable for medium-sized tractors, can be mounted to the front or rear, with three-point or A-frame hitches. Reinforced front propellers with ice breakers, lever-adjustable skid shoes, galvanized steel chute, hydraulic chute rotation, and hydraulic deflector adjustment. The augers are made with a serrated edge and reinforced to cut through hard-packed snow and ice. Adjustable skid shoes allow you to adjust the height of the cutting edge to save blowing gravel off of the pathway. Hydraulic chute rotation and deflector adjustment allow you to make adjustments without leaving the tractor cab.



	L 1300	L 1400	L 1500	L 1600
<b>Weight</b>	805 lbs (365 kg)	838 lbs (380 kg)	904 lbs (410 kg)	970 lbs (440 kg)
<b>Clearing Width</b>	51" (130 cm)	55" (140 cm)	59" (150 cm)	63" (160 cm)
<b>Overall Width</b>	53" (135 cm)	57" (145 cm)	61" (155 cm)	65" (165 cm)
<b>Intake Height</b>	33.5" (85 cm)			
<b>Overall Height</b>	71.5" (182 cm)			
<b>Cutting Auger Diameter</b>	20" (50 cm)			
<b>Oil Requirements</b>	14.5/32 GPM (55/120 l/min)	16/32 GPM (60/120 l/min)	18.5/32 GPM (70/120 l/min)	21/39.5 GPM (80/150 l/min)
<b>Impeller Diameter</b>	18" (45 cm)			
<b>Standard Features</b>	Reinforced frame, radial piston hydraulic motor, cast iron gearbox, auger with ice breaker, hydraulic chute rotation, hydraulic chute deflector adjustment.			
<b>Hitch Category</b>	Set-up for mounting plate or similar			
<b>Options</b>	Fully-adjustable chute in galvanized iron, electric chute rotation, electric chute deflector, vertical floating suspension, automatic safety torque limiters on auger.			

BUILT TO LAST

METEC METAL TECHNOLOGY INC.