HYD. RIBBON BLOWER -SUPER MIDDLE

L 1800, 2000

Suitable for large-sized skid-loaders, front-end loaders, and medium-sized wheel loaders. Adjustable skid shoes, galvanized steel chute, hydraulic chute rotation, and deflector adjustment. Heavy-duty serrated augers. Self-supporting front auger with ice breakers. Galvanized steel tilt-up chute for easy cleaning. The augers are made with a serrated edge and reinforced to cut through hard-packed snow and ice. Adjustable skid shoes allow you to adjust the height of the cutting edge to save blowing gravel off of the pathway. Hydraulic chute rotation and deflector adjustment allow you to make adjustments without leaving the tractor cab. Cast iron – self-bearing helices reducing friction for better performance.



	L 1800	L 2000
Weight	1,047 lbs (475 kg)	1,113 lbs (505 kg)
Clearing Width	71" (180 cm)	79" (200 cm)
Overall Width	73" (185 cm)	80.5" (205 cm)
Intake Height	33.5" (85 cm)	
Overall Height	72" (182 cm)	
Cutting Auger Diameter	20" (50 cm)	
Oil Requirements	26.5/37 GPM (100/140 l/min)	29/42 GPM (110/160 ℓ/min)
Impeller Diameter	22" (55 cm)	
Standard Features	Reinforced frame, radial piston hydraulic motor, cast iron gearbox, auger with ice breaker, hydraulic chute rotation, hydraulic chute deflector adjustment.	
Hitch Category	Set-up for mounting plate or similar	
Options	Fully-adjustable chute in galvanized iron, electric chute rotation, electric chute deflector, vertical floating suspension, automatic safety torque limiters on auger.	