

ROTARY MOWER - TRIPLEX

TH 2500, 3000 C

Want to save time? This mower, divided into three sections, is your solution! You'll be more than satisfied with the large cutting width provided by the five fixed knives. The hydraulic tilt-up is ideal for quick and easy maintenance and cleaning. For safety, the auto shut-off kicks in when knives are tilted at an angle of 30o or more. Offers a fully hydraulic or mechanical/hydraulic operation. Equipped with heavy-duty caster wheels.



	TH 2500 C	TH 3000 C
Weight	970 lbs (440 kg)	1,058 lbs (480 kg)
Cutting Width	98" (248 cm)	114" (290 cm)
Overall Width	100" (253 cm)	117" (298 cm)
Overall Height	20" (50 cm)	
Cutting Height	1-3" (3-8 cm)	
Power Requirements	34 HP (25 kW)	42 HP (31 kW)
Hydraulic Requirements	16 GPM (60 l/min)	19 GPM (70 l/min)
Height Adjustment	Hydraulic	
Number of Rotors	5 pcs	
Number of Knives	5 pcs	
Tires	6 pcs 10 x 3"	
Hitch Category	3-Point or A-Frame CAT I	
Options	Hydraulic Tilt-Up, Mulching kit, Chain guard, Rubber guard, Anti scalp disc, Flotation mounting frame, Foam filled puncture resistant wheels, Wide wheels included wheel fork	