

# ROTARY MOWER - TRIPLEX

## TH/THM 2500, 3000, 3500, 4000 C

Want to save time? This mower, divided into three sections, is your solution! You'll be more than satisfied with the large cutting width provided by the five fixed knives. The hydraulic tilt-up is ideal for quick and easy maintenance and cleaning. For safety, the auto shut-off kicks in when knives are tilted at an angle of 30° or more. Offers a fully hydraulic or mechanical/hydraulic operation. Equipped with heavy-duty caster wheels.



	TH/THM 2500 C	TH/THM 3000 C	TH/THM 3500 C	TH/THM 4000 C
<b>Weight</b>	970 lbs (440 kg)	1,058 lbs (480 kg)	1,367 lbs (620 kg)	1,543 lbs (700 kg)
<b>Cutting Width</b>	98" (248 cm)	114" (290 cm)	136" (346 cm)	158" (402 cm)
<b>Overall Width</b>	100" (253 cm)	117" (298 cm)	139" (352 cm)	162" (412 cm)
<b>Overall Height</b>	20" (50 cm)		24" (60 cm)	
<b>Cutting Height</b>	1-3" (3-8 cm)			
<b>Power Requirements</b>	34 HP (25 kW)	42 HP (31 kW)	51 HP (38 kW)	56 HP (42 kW)
<b>Hydraulic Requirements</b>	16 GPM (60 l/min)	19 GPM (70 l/min)	21 GPM (80 l/min)	23 GPM (85 l/min)
<b>Height Adjustment</b>	Hydraulic (mechanical option)			
<b>Standard Features</b>	Hydraulic Tilt-up, Heavy duty caster wheels, 7 fixed special knives, Automatic stop of knives when lifted more than 30°			
<b>Hitch Category</b>	3PH or A-Frame CAT I			
<b>Options</b>	Mulching kit, Chain guard, Rubber guard, Anti scalp disc, Flotation mounting frame, Foam filled puncture resistant wheels, Wide wheels including wheel fork			

BUILT TO LAST

METEC METAL TECHNOLOGY INC.