

# ROTARY MOWER - TRIPLEX

## TH/THM 2500, 3000

Want to save time? This mower, divided into three sections, is your solution! You'll be more than satisfied with the large cutting width provided by the five fixed knives. The hydraulic tilt-up is ideal for quick and easy maintenance and cleaning. Offers a fully hydraulic or mechanical/hydraulic operation. Mechanical cutting height adjustment



	TH/THM 2500	TH/THM 3000
<b>Weight</b>	805 lbs (365 kg)	970 lbs (440 kg)
<b>Cutting Width</b>	98" (248 cm)	114" (290 cm)
<b>Overall Width</b>	100" (253 cm)	117" (298 cm)
<b>Overall Height</b>	20" (50 cm)	
<b>Cutting Height</b>	1-3" (2-8 cm)	
<b>Power Requirements</b>	34 HP (25 kW)	42 HP (31 kW)
<b>Height Adjustment</b>	Hydraulic or Mechanical	
<b>Number of Rotors</b>	5 pcs	
<b>Number of Knives</b>	5 pcs	
<b>Tires</b>	6 pcs 10 x 3"	
<b>Standard Features</b>	Hydraulic lift of side mowers, Automatic stop of blades.	
<b>Hitch Category</b>	3-Point or A-Frame CAT 1	
<b>Options</b>	Hydraulic Tilt-Up, Mulching kit, Chain guard, Rubber guard, Anti scalp disc, Flotation mounting frame, Foam filled puncture resistant wheels, Wide wheels included wheel fork.	

BUILT TO LAST

METAL TECHNOLOGY INC.

**METEC**