

# TOW BEHIND SPREADER

## SKE 8, 15, 20

Meticulously designed to maintain a consistent delivery rate per square meter, regardless of changes in speed, ensuring a 100% road-speed correlation. The SKE spreader series boasts a robust construction across all models, each offering various hopper sizes to suit diverse needs. Specifically designed for towing behind tractors, these spreaders uphold Epoke's high standards with a comprehensive surface treatment process. This process includes sandblasting, zinc dust priming, a durable 2-component polyurethane base coat, and a finishing touch with a 2-component top coat.



	SKE 8	SKE 15	SKE 20
<b>Capacity</b>	1 cu yd (800 l)	1 1/2 cu yd (1,250 l)	2 cu yd (1,650 l)
<b>Weight</b>	882 lbs (400 kg)	1,323 lbs (600 kg)	1,587 lbs (720 kg)
<b>Spreading Width</b>	39.7" (101 cm)	54.7" (139 cm)	75.5" (192 cm)
<b>Overall Width</b>	50.6" (129 cm)	65.6" (167 cm)	86.4" (220 cm)
<b>Overall Height</b>	42.5" (108 cm)	51.2" (130 cm)	
<b>Standard Features</b>	Agitator, spring base, spring base adjustment, transmission, coupling, driving shaft and support wheel.		
<b>Hitch Category</b>	Toe hook		
<b>Options</b>	Electrical remote control, extra agitator.		

BUILT TO LAST

METAL TECHNOLOGY INC.

**METEC**