

BROADCAST SPREADER

Solid XG 1200, 1600, 2000

SOLID XG is a compact spreader designed for precise gritting and salt spreading in narrow areas like roads and footpaths. It features dry aggregate hoppers (0.6 to 1.5 m³) and liquid tanks (300, 400, and 500 l). The auger conveyor system ensures efficient spreading by preventing larger material lumps. Ideal for fine salt or stone granules, it allows mixing with chloride solutions using a pre-wetting system. Controlled by EPOS units, it provides precise spreading, travel-dependent application, asymmetrical pattern setting, and automated GPS spreading. Various mounting options are available based on the drive vehicle type.



	XG 1200	XG 1600	XG 2000
Dry Hopper Capacity	0.8 – 1 cu yd (0.6 – 0.8 m ³)	1 – 2 cu yd (0.8 – 1.5 m ³)	1.3 – 2 cu yd (1.0 – 1.5 m ³)
Liquid Tank Capacity	79.6 US G (300 l)	105.7 US G (400 l)	132.1 US G (500 l)
Spreading Width	39" – 236" (1 – 6 m)		
Control Unit	EPOS 5 - Fully dependent spreading, adjustment of spreading asymmetry image and control of spreading through feedback connections.		
Mounting	Custom options available		
Standard Features	Safety Grid and Cover		
Options	Control units EPOS 10 and EPOS 30, Pre-wetting system, transport system extension, sensors and cameras for spreading control, ARMS system, tarpaulins, access platform, storage legs, work lights and rotating lights, graphic markings, custom colours		

BUILT TO LAST

METEC METAL TECHNOLOGY INC.