

COUNTERWEIGHT - WHEEL LOADER

TRA-COUNTERWEIGHT

These counterweights are designed specifically for each tractor model and installed in as little as four hours. The loader arms are removed, allowing for a better view from the cab and an attachment that's much closer to the operator. Counterweights lower the centre of gravity and allow attachments like spreaders to be mounted at the rear. No modifications are required to the factory hydraulics. Three-point hitch attachments can be mounted without an adapter plate. The two independent lifting arms oscillate and are equipped with Oilite bronze bushings for corrosion resistance. They are also spaced for CAT 1 and CAT 2 hitches. Powder-coated for protection against corrosion. Model shown: Wacker Neuson WL32



TRA-COUNTERWEIGHT

| | |
|--------------------------|---|
| Weight | 2,500 lbs (1,134 kg) |
| Width | 39" (99 cm) |
| Length | 46" (117 cm) |
| Height | 34" (86 cm) |
| Standard Features | Low Profile, Hydraulic Pickup, No modifications required for installation |
| Hitch Category | CAT I or CAT II |
| Compatibility | Wacker Neuson WL28, WL32, Thaler 3448, Shaffer |
| Options | Custom Colours, 2" Round bar mount |

BUILT TO LAST

METAL TECHNOLOGY INC.

METEC