

# WEED CONTROL

## UK 425, 475, 725 R/L

Hydraulic operated weed brush for use with compact tractors, loaders and implement carriers. Hydraulic tilt in all 4 directions of brush head and hydraulic reach. (operates on left or right by mechanical swing over) Fitted with strong hydraulic engine with integrated shock suppression valve and reversible. Requires 1 x hydraulic double acting motor valve for operating and 3 x double acting valves for control.



BUILT TO LAST

METAL TECHNOLOGY INC.

**METEC**

	UK 425 R/L	UK 475 R/L	UK 725 R/L
<b>Weight</b>	408 lbs (185 kg)	474 lbs (215 kg)	694 lbs (315 kg)
<b>Sweeping Width</b>	43" (110 cm)		83" (210 cm)
<b>Width Folded</b>	39" (100 cm)		63" (160 cm)
<b>Overall Height</b>	35" (90 cm)		
<b>Power Requirements</b>	22 HP (16 kW)	26 HP (19 kW)	29 HP (21 kW)
<b>Brush diameter</b>	17" (43 cm)	24" (62 cm)	
<b>No. of Brushes/Tufts</b>	20 pcs	40 pcs	
<b>Standard Features</b>	Hydraulic tilt, integrated shock suppression		
<b>Hitch Category</b>	A-Frame or 3-Point CAT I or II		
<b>Options</b>	Extra crossover valve, Electric reversal kit, Hydraulic weight transfer, 40 pcs brushes (UK 425), 80 pcs brushes (UK 475, 725)		