

WATERING ARM

WA

Experience the convenience of operating the watering arm from inside the cab. With a water discharge rate of up to 20 gallons per minute, this advanced system efficiently waters hanging baskets, flower beds, trees, and more. Weighing 380 lbs, its compact design ensures easy maneuverability and storage, aided by convenient storage legs with locking caster wheels. Plus, the watering arm features an adjustable water head, allowing you to customize the watering angle for optimal effectiveness.



WA	
Weight	380 lbs (172 kg)
Height (arm collapsed)	90" (2.3 m)
Length (arm collapsed)	43" (1.1 m)
Width (arm collapsed)	38" (1 m)
Max Vertical Reach	153" (3.9 m)
Max Lateral Reach	145" (3.7 m)
Watering Head Pitch	-60° , +90°
Arm Swing Angle	170°
Water Head Diameter	2" or 4"
Water Discharge	Up to 20 GPM (96 ℓ/min)
Hydraulic Requirements	Arm Control: x3 circuits: 1 - 5 GPM (5 - 20 ℓ/min) - Max 3200 PSI/220 Bar Water Flow: x1 circuit: 5 - 29 GPM (20 - 110 ℓ/min)
Hitch Category	CAT I or II, Skid Steer Quick Attach
Standard Features	Storage Legs with Locking Caster Wheels, Adjustable Water Head Angle, Hydraulic Flow Control, Stainless Steel and Powder Coated Steel Finish

BUILT TO LAST

METEC METAL TECHNOLOGY INC.